## Third Rosenberg International Forum On Water Policy

# SALINITY MANAGEMENT IN THE NILE DELTA CASE STUDY :REUSE OF DRAINAGE WATER IN EGYPT

DR. ABDEL FATAH METAWIE

Canberra, Australia October 7-11<sup>th</sup>, 2002


#### Introduction

#### Challenges

- Limited Water Resources:
  - Fixed Fresh Water Share.
  - Arid Climate.
  - Limited Safe Ground Water Abstraction.
- \* Rapid Population Growth:
  - Population: 67 million in 2002.
- **®**Environmental degradation:
  - Water Salinity.
  - Water Quality Problems.

## Introduction Cont.

**\*Limited Share of Water Per Capita** 




## Introduction Cont.

**® High Population Density:** 

- Nile Valley Area
  - = 4% of the Total Area.

- Population Density
  - = 1200 inhabitants/Km<sup>2</sup>.




## Available Water Resources

Water Supply	Present	<b>Future (2017)</b>
Surface Water	55.5	55.5
Deep Ground Water (Renewable & Non)	5	6
Rainfall & Harvested Flash Floods	1.0	1.5
Total	61.5	63.0

#### **Available Water**

Resources

WATER RESOURCES (EGYPT)



## Projected Water Demand and Deficit

#### **Water Demands**

- Agriculture
- Domestic
- Industry
- Navigation

#### **Present**

- 61.5
- 4.5
- 7.5
- 0.5

#### 2017

- 66.5
- 7.0
- 12.5
- 0.0

**Total** 

74

86

**Deficit** 

12.5

**23** 

### Solution: Water Use Utilization

#### **Water Use Utilization**

#### **Utilization**

- Drainage Water Reuse
- Irrigation Improvement (Drip, spray, .)
- Increasing Groundwater Potential
- Sea Water desalinization (Coastal Areas)
- Treated Sewage Water
- Improved Crop Patterns

#### **BCM**

- 4.0
- 4.0
- 2.0
- 0.5
- 2.0
- 3.0

**Total** 

**15.5** 

### SALINITY MANAGEMENT

The Major Sources Of Water Pollution in River Nile are:

Municipal & Rural domestic sewage

Industrial water & Agriculture chemical

 Egypt & Netherlands jointly execute the project "Monitoring and Analysis of Drainage water Quality" "MADWQ project"

## 1-1) Project objectives

 Implementation of measuring network to monitor drainage water quality in Nile-delta and Fayoum.

Use of mathematical models to support drainage water management.

 Systematic publication of data and datainterpretation

Enhancing research capacity at DRI.

### Immediate Objectives of the Project are:

 Upgrading of the already existing monitoring network.

 Extension of the drainage monitoring network to coverall critical sites.

 Establishments of a database on the pollution drainage systems.

## Immediate objectives of the project are (cont.)

Cost-effective upgrading of the field

 Development of interpretation tools and protection models.

 As certain the availability of water quality and load models.

 Strengthening DRI with the well trained staff in water pollution, field sample.

#### 3) Achievements:

An integrated measuring network.

The Use of numerical simulation models

The research capacity at DRI.

Systematic publication of Data and Data interpretation

#### 3) Project implementation

 It started with the reconnaissance water quality survey, to obtain general insight in the water quality status.

 Monitoring program at selected points was designed for detailed insight in the water quality.

Finally the quantity and quality programs were integrated into one program

### 4) NET WORKS DESEIGN IMPLEMENTATION

4.1) RECONNAISSANCE SURVERY NETWORK.

The total number of parameters was 34 taking into consideration.

Microbiological& The classic parameters


Oxygen related parameters.

Nutrients and extended cations.

Table.4.1. Number of monitoring locations in different regions included in the reconnaissance survey.

	Number of locations			
Region	Existing Monitoring	Additional	Total	
	Program			
Eastern-Delta	34	39	73	
Middle-Delta	32	38	70	
Western-Delta	29	40	69	
Fayoum area	-	17	17	
Reference point	-	1	1	
Total	95	135	230	


### The monitoring network of the Nile delta



## 4.2 Automated Water Quality Monitoring Stations

 Four automated Water Quality Monitoring Station (CWQMS) were installed at strategic locations in the Nile Delta.

 Desk Study has been carried to identify sources of pollution to the drainage system.



Locations of the continuous water quality monitoring stations in the Nile Delta

- Intake of Hanout Irr. Pump station at Bahr Hadous Darin;
- Intake of EI-Salam 3 pump stations at Bahr Hadous drain;
- Intake of Hamul Irr. Pump station at Gharbia main

## 5) INFORMATION MANAGEMENT

- The supporting tools for managing to the end users are:
- A powerful relational database capable of handling huge amounts of data.

Simulation models for evaluation the changes in surface water quality.

### 6) Modeling

 The SIWARE model & the three Delta models have been adjusted for integration to evaluate different water management strategies for the future.

- the input of SIWARE are:
  - The reuse of drainage water plans
  - The irrigation methods.
    - The municipal use of surface water

## 7) Drainage water quality status

 An extensive survey is available of the water quality in drainage system in the Nile Delta and Fayoum


 Data are now available for the years 1996-2000 and will be extended to allow for more analyses.

 The present monitoring results indicate that all drains suffer from domestic discharges and some drains receive • The most polluted drains are:

The Bahar El Baqar in the Eastern Delta.

The Gharbia drain in the middle delta

The Umoum and Abu-Keer drins in the Western Delta.



Average BOD concentration in the Nile delta 1997



Av. Dissolved
Oxygen
concentration in
the Nile delta
1997


#### 8) FUTURE DEVELOPMENT

- Preparation of the Central Laboratories for Environmental Quality Monitoring.
- The Drainage -monitoring networks is expanded into a national network.
- As more data become available, the statistical analysis for the data will be possible.
- computer models and techniques are expanded to include prediction of certain


	total executed	executed	first plan	second plan	third plan	forth plan	proposal in	proposal in
activity	uptill 30/6/2002	before 1982	1982-1987	1987-1992	1992-2997	1997-2002	2002-2007	2007-2012
	area	area	area	area	area	area	area	area
Nile Delta	3728	1640	509	507	552	520	500	372
Nile valley	1465	608	332	220	168	137	150	185
Total of subsurface	5193	2248	841	727	720	657	650	557
drainage								

	total executed	executed	first plan	second plan	third plan	forth plan	proposal in	proposal in
activity	uptill 30/6/2002	before 1982	1982-1987	1987-1992	1992-2997	1997-2002	2002-2007	2007-2012
	cost	cost	cost	cost	cost	cost	cost	cost
Nile Delta	1670	310	124	277	459	500	720	600
Nile valley	782	130	82	107	213	250	292	300
Total of subsurface drainage	2452	440	206	384	672	750	1012	900

#### Implementation Program Of Subsurface drainage up to 2017



#### Implementation Program Of Subsurface drainage up to 2017



■ Nile Delta
■ Nile valley

# Thank you for your attention